


Islandaire EZ Series RG is a replacement for the custom-sized 30" by 16" packaged terminal air conditioning units. Our commercial duty construction with heavy gauge galvanized steel and superior components create an efficient and reliable unit. This design eliminates the need for any interior or exterior renovation. Use of the existing wall sleeve-cabinet and louver saves time and money, two very important factors in today's competitive environment! If the need does occur where the wall sleeve-cabinet, hydronic coil, and/or louver needs to be replaced, we manufacture these accessories as well.




FEATURES

- Proudly Assembled in the U.S.A.
- ETL listed products
- Superior Energy Efficiency Ratios (EERs)
- Commercial Duty Construction with Heavy Gauge Galvanized Steel
- Designed for exact replacement of existing sleeve opening
- Energy Efficient Rotary Compressors
- P.S.C. Evaporator and Condenser Motors
- High-Efficiency Refrigeration Coils Used to Provide Superior Heat Transfer
- Units Available as Cooling only, Cooling with Electric Heat, Cooling with Hydronic Heat
- Custom Options Available
- Available with wired and wireless wall thermostats
- NYC MEA Number 358-93-E Vol. II



*Specifications are subject to change due to ongoing product development.

6140606 Rev. - (11/26/24)




MODELS

	EZ09			EZ12		
VOLTS	115	208 / 230	277	115	208 / 230	277
BTUH COOL	9,200	9,200	9,400	11,800	12,000	11,500
AMPS	8.87	4.86 / 4.39	3.77	12.22	6.08 / 5.5	4.89
WATTS COOL	1,020	1,010	1,045	1,405	1,265	1,355
EER	9.0	9.1	9.0	8.4	9.5	8.5
CFM HIGH	400	400	400	420	420	420
CFM LOW	260	260	260	350	350	350
WEIGHT (LBS)	110	110	110	115	115	115

* CFM values are dry coil (not in cooling mode).

Where applicable, cooling capacities are specified at conditions of 95 °F DB/75 °F WB (35 °C DB/24 °C WB) outdoor and 80 °F DB/67 °F WB (27 °C DB/19 °C WB) indoor and heating capacities are specified at conditions of 47 °F DB/43 °F WB (8 °C DB/6 °C WB) outdoor and 70 °F DB/60 °F WB (21 °C DB/16 °C WB) indoor in accordance with AHRI 310/380 and CSA C744 standards. Wattage, Amperage, EER, and COP listings include compressor, evaporator motor and condenser fan motor. The above ratings are a typical heat pump style unit.

Line Voltage	Maximum Amperage	Wall Socket Configuration	Receptacle Number	Electrical Heat Options
115	12		NEMA 5-15R	1.3
115	16		NEMA 5-20R	1.7
208/230	12		NEMA 6-15R	2.0 - 2.5
208/230	16		NEMA 6-20R	3.4
208/230	24		NEMA 6-30R	4.2 - 5.0
277	16		NEMA 7-20R	2.0 - 4.2
277	24		NEMA 7-30R	5.0




Heating Option	Voltage (1)	Wattage	BTU/h	Amps (2)
B	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
C	208	2,945	10,100	14.16
	230	3,600	12,300	15.65
	277	3,600	12,300	13.00
D	208	3,435	11,700	16.51
	230	4,200	14,300	18.26
	277	4,200	14,300	15.16
E	208	4,090	14,000	19.66
	230	5,000	17,100	21.74
	277	5,000	17,100	18.05
H	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
I	208	2,945	10,000	14.15
	230	3,600	12,300	15.65
	277	3,600	12,300	13.00
Y	115	1,300	4,400	11.30

(1) Voltage is Single Phase, Alternating Current and R.M.S.

(2) Amp values are for heater element only.


ENCLOSURES

PART NUMBER	DESCRIPTION	APPROX. WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4083029	EZRG Enclosure Assembly w/adjustable base. Depth available in 1" increments (10.5" min.).	50 lbs. (approx.)	various	40"	24" - 27"




WALL SLEEVE

PART NUMBER	DESCRIPTION	APPROX. WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
2400642	EZRG Panel Wall Sleeve. Depth available in 1" increments.	25 lbs.	various	30 1/2"	16"
2400233	EZRG Masonry Wall Sleeve. Depth available in 1" increments.	25 lbs.	various	30 1/2"	16"




HYDRONIC COILS

PART NUMBER	DESCRIPTION	APPROX. WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4090285	EZRG Hydronic Coil Assembly	20 lbs.	9 1/4"	32 1/2"	3 3/4"



LOUVERS

PART NUMBER	DESCRIPTION	APPROX. WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6070191	EZRG Architectural Louver	10 lbs.	1 1/8"	30"	15 11/16"




THERMOSTATS

PART NUMBER	DESCRIPTION	APPROX. WT.	FEATURES		
			CONNECTION	STAGE	DISPLAY
6041206	Islandaire Non-Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041210	Islandaire Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041228	Islandaire Programmable (7 Day/5-1-1 Day/Non-Programmable), Two Fan Speed	1.0 lbs.	Wired	Single	Horizontal
6041373	Islandaire Wireless, WiFi Programmable	1.0 lbs.	Wireless	Single	Horizontal



FILTERS

PART NUMBER	DESCRIPTION	APPROX. WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6080021	EZRG Aluminum Filter, Standard	2 lbs.	0.250"	23 13/16"	8"



**Ask your salesman about
our DR. PTAC option!***



*100% conditioned
fresh air

EZ Series VH Unit Available

Vertical Water Source Hybrid Heat
Pump, Replacement For:

CGC InnKeeper/HomeKeeper



Scan for more information

500 Middle Country Road, St. James, NY 11780 • 1-800-886-2759

e-mail: sales@islandaire.com • www.islandaire.com

Ph: 631-471-2900 • Fax: 631-471-2913



Locally Represented By: