


Console Water Source Replaces Cool Heat Water Cooled Hydronic Heat


Islandaire "The Perfect Fit" units are designed to exactly replace the original, existing chassis! No field modification kits or builder renovations are required. Islandaire units are designed for optimal efficiency and reliability.

This appliance is intended for new construction or replacement of Cool Heat water source units. Please confirm that the electrical rating of this appliance matches the electrical supply available before beginning installation.



Features:


- Proudly Assembled in the U.S.A.
- Superior energy efficient ratio (EER)
- High efficiency coaxial condenser coil
- High efficiency evaporator coil
- Commercial duty construction with heavy gauge galvanized steel
- High pressure protection
- Compressor and water circuit freeze protection
- Refrigerant circuit access ports
- Float Switch provided as standard equipment



New Room Cabinet required (part number 4080483)

*Specifications are subject to change due to ongoing product development.

6140672 Rev. - (9/30/25)



ENVIRONMENTALLY
SOUND
REFRIGERANT



Slide the old LC unit out, slide
"The Perfect Fit" Islandaire unit in!
No Renovations!

MODELS

	EZ07			EZ09			EZ12		
VOLTS	115	208/230	277	115	208/230	277	115	208/230	277
BTUH COOL	8,100	7,900/8,100	8,100	9,300	9,100/9,300	9,300	12,200	12,000/12,200	12,200
AMPS COOL	5.04	2.72/2.52	2.09	6.00	3.25/3.00	2.49	7.78	4.23/3.89	3.23
WATTS COOL	580	565/580	580	690	675/690	690	895	880/895	895
EER	14.0	14.0/14.0	14.0	13.5	13.5/13.5	13.5	13.6	13.6/13.6	13.6
CFM (m3/min) HIGH ⁽¹⁾	420 (11.9)	410 (11.6)/ 420 (11.9)	420 (11.9)	420 (11.9)	410 (11.6)/ 420 (11.9)	420 (11.9)	460 (13.0)	450 (12.7)/ 460 (13.0)	460 (13.0)
CFM (m3/min) LOW ⁽¹⁾	280 (7.9)	270 (7.6)/ 280 (7.9)	280 (7.9)	280 (7.9)	270 (7.6)/ 280 (7.9)	280 (7.9)	320 (9.1)	310 (8.8)/ 320 (9.1)	320 (9.1)
GPM (L/min)	2 (7.6)	2 (7.6)/2 (7.6)	2 (7.6)	2 (7.6)	2 (7.6)/2 (7.6)	2 (7.6)	3 (11.4)	3 (11.4)/3 (11.4)	3 (11.4)
C.O.P.	4.6	4.6/4.6	4.6	4.5	4.5/4.5	4.5	4.6	4.6/4.6	4.6
BTUH HEATING	9,600	9,400/9,600	9,600	12,000	11,800/12,000	12,000	15,000	14,800/15,000	15,000
AMPS HEATING	5.30	2.88/2.65	2.20	6.78	3.70/3.39	2.82	8.30	4.54/4.15	3.45
WATTS HEATING	610	600/610	610	780	770/780	780	955	945/955	955
SOUND LVL (dBA) ⁽²⁾	48	48	48	51	51	51	53	53	53
WEIGHT, LB. (kg)	85 (39)	85 (39)	85 (39)	90 (41)	90 (41)	90 (41)	95 (43)	95 (43)	95 (43)

⁽¹⁾ CFM values are dry coil (not in cooling mode).

⁽²⁾ Sound values represent sound pressure levels.

Notes:

1) Data based on AHRI/ASHRAE/ISO 13256-1:

Cooling (EAT): 80.6 °F DB\66.2 °F WB

Cooling (EWT): 86.0 °F

Heating (EAT): 68.0 °F DB\59 °F WB


Heating (EWT): 68.0 °F

2) Water Loop Operation

Cooling LWT - EWT = 10 °F


Heating EWT - LWT = 10 °F

Line Voltage	Maximum Amperage	Wall Socket Configuration	Receptacle Number
115	16		NEMA 5-20R
208/230	12		NEMA 6-15R
208/230	16		NEMA 6-20R
208/230	24		NEMA 6-30R
277	16		NEMA 7-20R



ENCLOSURES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4085953-00	EZ Series LC Enclosure Assembly	37.0 lb.	13.500"	50.000"	16.500"



HOSE KITS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS	
			LENGTH	DIA.
4091501	Hose Kit, 1/2", 2.00 GPM, 18"L	3.0 lb.	18.0"	1/2"
4091683	Hose Kit, 1/2", 2.00 GPM, 18"L, w/Strainer	3.0 lb.	18.0"	1/2"
4091261	Hose Kit, 1/2", 2.00 GPM, 24"L	3.0 lb.	24.0"	1/2"
4091669	Hose Kit, 1/2", 2.00 GPM, 24"L, w/Strainer	3.0 lb.	24.0"	1/2"
4091576	Hose Kit, 1/2", 3.00 GPM, 18"L	3.0 lb.	18.0"	1/2"
4091685	Hose Kit, 1/2", 3.00 GPM, 18"L, w/Strainer	3.0 lb.	18.0"	1/2"
4091577	Hose Kit, 1/2", 3.00 GPM, 24"L	3.0 lb.	24.0"	1/2"
4091671	Hose Kit, 1/2", 3.00 GPM, 24"L, w/Strainer	3.0 lb.	24.0"	1/2"



MOTORIZED VALVES

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES		
			VOLTAGE	TYPE	INLET
6041215	Actuator, 24 Vac, Normally Closed	1.0 lb.	24 Vac	NC	N/A
6041256	Actuator, 24 Vac, Normally Open	1.0 lb.	24 Vac	NO	N/A
6041214	Valve Body, 1/2" Thread, NPT	1.0 lb.	N/A	N/A	NPT



THERMOSTATS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES		
			CONNECTION	STAGE	DISPLAY
6041206	Islandaire Non-Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041210	Islandaire Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041228	Islandaire Programmable (7 Day/5-1-1 Day/Non-Programmable), Two Fan Speed	1.0 lbs.	Wired	Single	Horizontal
6041373	Islandaire Wireless, WiFi Programmable	1.0 lbs.	Wireless	Single	Horizontal




FILTERS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6080028	EZ Series LC Aluminum Filter, Standard	2.0 lb.	0.250"	26.000"	7.000"



OTHER OPTIONS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES
6041223	Strainer, 1/2" Dia. Hose Kit	1.0 lb.	Use with 1/2" dia. Hose Kit



**Ask your salesman about
our DR. PTAC option!***



*100% conditioned
fresh air

EZ Series VH Unit Available

Vertical Water Source Hybrid Heat
Pump, Replacement For:

CGC InnKeeper/HomeKeeper



Scan for more information

500 Middle Country Road, St. James, NY 11780 • 1-800-886-2759

e-mail: sales@islandaire.com • www.islandaire.com

Ph: 631-471-2900 • Fax: 631-471-2913



Locally Represented By: